



WB10 Series Camera

The Case WB10 Camera is a 8MP waterproof bullet camera with 10x Optical Motorized Zoom and is IP 66 Waterproof.

The WB10 camera comes with Case Lite software for Content Management System (CMS) and Real Time Operating System (RTOS).

The Case WB10 CAMERA Is assembled in the United States. All Case Video Analytic Software is designed, built, and developed in the United States.

The WB10 camera also comes in a 5MP version: Model WB10-5MPC.

Embedded RTOS Resign, Image Sensor 1/2.8" CMOS Sensor.

5 Megapixel Resolution DSP Dual core (HI3516E) Min. Illumination Color 0.01Lux@F1.2, B/W 0.01 Lux@F1.2 Adjust Parameters DWDR, BLC, DNR, AE, AGC, D&N, Mirror, Flip and more.

Case 10x Camera Day-Night Outdoor 5MP IR Camera

Video: H.265 Primary Compression
Stream: Dual stream, AVI format
Bitrate: Support 0.1M-8Mbps Adjustable-Bitrate

Frame Rates: Support 1-30 FPS Adjustable

Audio Input/Output: 1CH input
(Microphone Optional)
Compression: G.711 Compression
Supports Two-way Audio Intercom, Audio and Video Synchronized Output

Alarms: Motion Detection, Tamper Alarm, and Video Loss.

General: Web Browser Support, Smart Phone Support, Case CMS Software (multiple device management system)

Network: RJ45: 10/100M Support
RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP/ONVIF/PoE

Language: English, Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, Chinese, Turkish, and others.

IR Filter Set of double light switch IR-CUT Filter

Lens Mount: 10x Varifocal Lens 5-50mm
Infrared Luminary SMD IR LED (6)
Wavelength 850nm
Distance: 40m

Model No.	WB10-8MPC	WB10-5MPV	WB10-2MPC
Camera Type	WB10 Series		
	5MP Bullet CCTV Camera 3.6mm Fixed Lens Night Vision Outdoor Camera		
Effective Pixels	8.0 Mega Pixels	5.0 Mega Pixels	2.0 Mega Pixels
Image Sensor	1/2.8" SONY IMX415 CMOS Sensor	1/2.8" SONY IMX335 CMOS Sensor	1/2.8" SONY IMX307 CMOS Sensor
DSP	FH8556	FH8538	FH8536
Min. Illumination	Color 0.01Lux@F1.2		
	B/W 0.01 Lux@F1.2		
Signal System	AHD/TVI/CVI/CVBS or PAL/NTSC		
On Screen Display	Yes,Cable Control/UTC		
OSD Function	Manual/DC Lens,Shutter/AGC/WB,Pict Adjust,Mirror,Day/Night,DNR,BLC/HLC,Motion Detect,Privacy Zone		
IR Cut Filter	IR LED synchronous switching double filter		
Lens Mount	Fixed Lens 4mm		
Infrared Luminary	4pcs New Array IR LEDs		
Infrared Wavelength	850 nm		
Illuminate Distance	40m		
Waterproof Criterion	IP65		
I/O Connector	1*DC Power Connector ,1* BNC Video Connector/POE		
Supplied Voltage	DC12V		
Power Consumption	Less than 200mA		
Working Enviroment	(-10°C~+60°C, 10%~90% (Built in Heater being optional added for enviroment lower than -20°)		
Weight	0.60KG		
Case Technology Solutions All Rights Reserved ▪ www.case-ts.com ▪ 281-761-7009 ▪ sales@case-ts.com			